

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁵ : A47C 23/06, 31/12</p>	<p>A1</p>	<p>(11) International Publication Number: WO 91/01099 (43) International Publication Date: 7 February 1991 (07.02.91)</p>
<p>(21) International Application Number: PCT/NL90/00098 (22) International Filing Date: 19 July 1990 (19.07.90) (30) Priority data: 8901866 19 July 1989 (19.07.89) NL (71) Applicants (for all designated States except US): NORMA BOXMEER B.V. [NL/NL]; Ir. Wagterstraat 15, NL-5831 AZ Boxmeer (NL). MATRASSENFABRIEK EASTBORN B.V. [NL/NL]; P.O. Box 62, NL-7680 AB Vroomshoop (NL). OOST SLAAPCOMFORT B.V. [NL/NL]; P.O. Box 4176, NL-1009 AD Amsterdam (NL). (72) Inventor; and (75) Inventor/Applicant (for US only): JURRIUS, Hermanus, Johannes, Wilhelmus, Bernardus [NL/NL]; De Nachtegaal 1, NL-2104 BN Heemstede (NL).</p>		<p>(74) Agent: SMULDERS, Th., A., H., J.; Vereenigde Octrooibureaux, Nieuwe Parklaan 107, NL-2587 BP The Hague (NL). (81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CM (OAPI patent), DE*, DE (European patent)*, DK, DK (European patent), ES, ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL, NL (European patent), NO, RO, SD, SE, SE (European patent), SN (OAPI patent), SU, TD (OAPI patent), TG (OAPI patent), US. Published With international search report. In English translation (filed in Dutch).</p>
<p>(54) Title: MATTRESS OR MATTRESS SUPPORTING STRUCTURE</p> <div data-bbox="446 1186 1177 1753"> </div> <p>(57) Abstract</p> <p>Mattress or mattress supporting structure (3) comprising a plurality of slats (7) interconnected by means of flexible material, the slats being each supported by a spring means (8), and this combination being integrated in a synthetic foam composition (9), and in which the slats (7) or the resilient means (8) supporting them are readily replaceable. A variant is formed by coupling the resilient means and the synthetic foam composition to form a single resiliently elastic strip (20).</p>		

DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MC	Monaco
AU	Australia	FI	Finland	MG	Madagascar
BB	Barbados	FR	France	ML	Mali
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GR	Greece	NL	Netherlands
BJ	Benin	HU	Hungary	NO	Norway
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	SD	Sudan
CF	Central African Republic	KP	Democratic People's Republic of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SN	Senegal
CH	Switzerland	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
DE	Germany, Federal Republic of	LU	Luxembourg	TC	Togo
DK	Denmark			US	United States of America

Title: Mattress or mattress supporting structure

This invention relates to a mattress or a mattress supporting structure comprising a plurality of slats interconnected by means of flexible material. It is an object of the invention to render such a slatted base, which is known per
5 se, more flexible.

To this effect, the mattress or mattress supporting structure is characterized in that the slats are each supported by a spring means and this combination is integrated in a resilient mass, such as, for example, foam plastic.

10 By mounting the slats and/or the resilient means so that they are readily replaceable, it is possible, in a simple manner, starting from a basic number of parts, to bring about a mattress or mattress supporting structure with a unique resilient character.

15 This last can also be effected by using slats and/or spring means having different spring characteristics.

Yet another possibility consists in making the slats and/or the resilient means lengthwise with variable spring characteristics.

20 The whole may be housed in a cover.

In a further elaboration of the invention, the mattress or mattress supporting structure may consist of a plurality of parts constructed according to the above, and these parts may be hingedly connected together for easy adaptation to beds
25 whose supporting surface consists of a plurality of parts which can be set at an angle to each other.

Furthermore, the supporting structure may be supported by a rigid frame. This rigid frame may be connected through a resilient connection to a bed frame disposed outwardly of said rigid frame.

5 Furthermore, the mattress or mattress supporting structure may be covered in known manner by a mattress protecting underlay.

In accordance with a different embodiment of the invention, the bed is characterized in that the flexible material
10 and the spring means are coupled to form one single resiliently elastic strip.

In illustration of the invention, one embodiment of a bed provided with a mattress or mattress supporting structure will now be described, by way of example, with reference to the
15 drawings. In said drawings:

Fig. 1 shows a perspective view of the bed according to the invention, but with the parts shown in spaced relationship to each other;

Fig. 2 shows, on a larger scale, the detail indicated by
20 A in Fig. 1;

Fig. 3 shows a side-elevational view of a second embodiment of the bed according to the invention;

Fig. 4 shows, on an enlarged scale, a cross-sectional view, taken on the line IV-IV of Fig. 3;

25 Fig. 5 shows a perspective, partially exploded view similar to Fig. 1 of a different embodiment of the mattress supporting structure according to the invention; and

Fig. 6 shows, on an enlarged scale, a detail of the structure of Fig. 5.

According to the drawings, a bed according to the invention includes a surrounding structure or bedstead 1 with legs 2. In the surrounding structure, a mattress supporting structure 3 can be disposed, on the top of which a mattress 4 can rest. As best shown in Fig. 1, the mattress supporting structure 3 is composed of a plurality of parts 5 interconnected by means of hinges 6.

As clearly shown in Fig. 2, each part 5 consists of a plurality of slats 7, each supported by a resilient member 8. Each combination of slat and resilient element is received in a resilient, in this case foam plastic composition 9. The mattress supporting structure is covered with a mattress protecting underlay 10. The mattress supporting structure is, as a whole, housed in a cover not shown in Figs. 1 and 2.

This cover is present in the embodiment shown in Figs. 3 and 4 and designated by 11.

As shown by these latter two figures, the mattress supporting structure is in turn supported by a support 12 which by means of a resilient hinge 13 is connected to a bed frame 14. For the rest, the embodiment of Figs. 3 and 4 corresponds fully to that according to Figs. 1 and 2, so that it will not be described further herein.

Instead of bed frame 14, use can be made of a tuck-in edge fixedly connected to support 12.

The embodiment illustrated in Figs. 5 and 6 differs from that shown in Figs. 1-4 to the extent that, in the second embodiment, the slats are supported by a resilient plastic strip 20 which in essence is a combination of the resilient member 8 and the plastic foam composition 9 in the arrangement of Figs. 1-4. The plastic strip 20 is provided with recesses 21 for receiving slats 7.

Plastic strip 20 is, in turn, received in a U-shaped section 22 essentially consisting of a plurality of parts 23 articulated together, as best shown in Fig. 6.

To this effect, the resilient members 23 are connected together by a joint 24 constructed and arranged so that the axis of rotation is in each case at the top of the U-shaped support. It is thus ensured that the support members can pivot relative to each other into a desired raised position. As, however, there should also be a possibility for the parts to move in a different direction relative to each other, the joints are V-shaped opening downwardly, so that this joint can also move upwards relative to the U-shaped section.

The U-shaped sections 22 are carried by supports 25 interconnected by means not shown to jointly form a bed frame.

Fig. 6 additionally shows, schematically, known per se resiliently operable rods for moving parts 23 relative to each other.

It will be clear that a large number of modifications are possible within the scope of the invented idea.

CLAIMS

1. Mattress or mattress supporting structure comprising a plurality of slats interconnected by means of flexible material, characterized in that the slats are each supported by a spring means and this combination is integrated in a synthetic
5 foam composition.
2. Mattress or mattress supporting structure as claimed in claim 1, characterized in that the slats or the spring means supporting them are readily replaceable.
3. Mattress or mattress supporting structure as claimed in
10 claim 1 or 2, characterized in that the slats and/or the spring means supporting the slats have different spring characteristics.
4. Mattress or mattress supporting structure as claimed in claim 1, 2 or 3, characterized in that the slats and/or the
15 spring means supporting the slats have different spring characteristics in the longitudinal direction.
5. Mattress or mattress supporting structure as claimed in one or more of the preceding claims, characterized in that the whole is housed in a cover.
- 20 6. Mattress or mattress supporting structure as claimed in one or more of the preceding claims, characterized in that the mattress supporting structure consists of a plurality of parts constructed according to claims 1-4, and these parts are hingedly connected together.

7. Mattress or mattress supporting structure as claimed in one or more of claims 1-5, characterized in that the mattress or mattress supporting structure is supported by a rigid frame.

5 8. Mattress or mattress supporting structure as claimed in claim 7, characterized in that the rigid frame is connected through a resilient connection to a bed frame disposed outwardly^{en} of said rigid frame.

9. Mattress or mattress supporting structure as claimed in
10 one or more of the claims, characterized in that the supporting structure is covered in known manner by a mattress protecting underlay.

10. Mattress or mattress supporting structure as claimed in one or more of the preceding claims, characterized in that the
15 flexible material and the spring means are coupled to form one single resiliently elastic strip (20).

11. Mattress or mattress supporting structure as claimed in claim 10, characterized in that said resiliently elastic strip (20) is received in a U-shaped section (22) forming part of a
20 frame supporting the mattress or mattress supporting structure.

12. Mattress or mattress supporting structure as claimed in claim 11, characterized in that said U-shaped section consists of a plurality of articulated parts.

25 13. Mattress or mattress supporting structure as claimed in claim 12, characterized in that the axes of rotation of the

joints are at the top of the U-shaped sections or section parts in the mounted condition thereof.

14. Mattress or mattress supporting structure as claimed in claim 12 or 13, characterized in that the U-shaped supporting parts are beveled at the joints so that in the straight condition of the parts a downwardly open V-shaped construction is formed at the joint axes, so that the parts can also be moved relative to each other in such a manner that the joint axis can move upwardly relative to the remaining part of the U-shaped support.

1/4




FIG. 1




FIG. 2

2/4




FIG. 4




FIG. 3




FIG. 5

4/4




FIG. 6

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

International Application No

PCT/NL 90/00098

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
Int.Cl. 5 A47C23/06 ; A47C31/12		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl. 5	A47C	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT ⁹		
Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
Y	EP,A,0186264 (GRIFFIN) 02 July 1986 see column 1, line 50 - column 2, line 12; figure 1	1
A	---	2, 5, 7, 10
Y	EP,A,0211772 (MERINOS) 25 February 1987 see page 3, line 8 - page 5, line 25 see page 6, lines 4 - 7 see page 7, lines 17 - 33; figures	1
A	---	6, 7, 10
A	EP,A,0011755 (PRB) 11 June 1980 see page 3, line 34 - page 4, line 14; figures 3-7	2, 3, 4
A	FR,A,2490473 (MARTINEZ) 26 March 1982 see page 2, line 37 - page 3, line 13; figures	10, 11, 12
<p>¹⁰ Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the International filing date</p> <p>"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the International filing date but later than the priority date claimed</p> <p>"T" later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
26 OCTOBER 1990	14. 11. 90	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	M. Peis	
	M. PEIS	

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

NL 9000098
SA 38880

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 30/10/90

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0186264	02-07-86	GB-A, B 2164550	26-03-86
		AU-B- 577121	15-09-88
		AU-A- 4315585	27-03-86
		JP-A- 61094611	13-05-86
EP-A-0211772	25-02-87	FR-A, B 2586345	27-02-87
EP-A-0011755	11-06-80	LU-A- 80505	05-06-80
FR-A-2490473	26-03-82	None	